

VOX

KHROMA COLLECTION

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Needlefelt Aiguilleté Nadelvlies Naaldvilt	FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	EN ISO 105-B02 ≥ 5-6
--	---	--	-------------------------

PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PP	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 3-4
---	---------	---	-------------------------

SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Bitumen back Min. 70% recycled content	FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 B _{FL-s1} if glued
---	---	---	---

PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 650 gr/m ²	SIZE DIMENSION ABMESSUNG AFMETING	50 X 50 cm
---	-------------------------	--	------------

TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.850 gr/m ²	PACKAGING EMBALLAGE VERPACKUNG VERPAKKING	5 m ² /b 20 b/p
--	---------------------------	--	-------------------------------

PILE THICKNESS EPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 4,5 mm		
---	----------	--	--


TOTAL THICKNESS EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE	± 6,0 mm		
--	----------	--	--

PRODIS / GUT	B7CC80D9		
---------------------	----------	--	--

CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 22 - LC2		
---	---------------------	--	--



02/23 All rights reserved to alter technical specification
 Sous réserve de modifications techniques
 Unter Vorbehalt von technischen Änderungen
 Onder voorbehoud van wijzingen van de technische specificaties.



EN 14041 CE
22
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1022#BJOABV
Textile Floor Covering EN 13297 Notified body 2401




Impressum / Imprint