

# Technical Data Sheet

planeo click vinyl rigid with no impact sound insulation

Country house decors

## Dimension

Length	1220 mm
Width	178 mm
Thickness	3,5 mm

## Structure

Wear layer	0,2 mm
Bevel	no Bevel

## Floor finish

PU Finish

## Connection

Click system

## Country of manufacture

China

## Packaging

1 package = 8/9 planks	1,737 m <sup>2</sup>	1,954 m <sup>2</sup>
1 pallet = 45/40 packages = 360 planks	78,165 m <sup>2</sup>	78,160 m <sup>2</sup>

## Properties

EU classification	EN685	21 und 22
Wear	EN649	T
Fire protection	EN13501-1	B <sub>fl</sub> -s1
Slip resistance	EN13845 (DIN51130)	DS; R10
Residual pressure	EN433	passed
Light fastness	ISO105B02	≥ 6
Chemical resistance	EN423	passed
Formaldehyde emission	EN717-1	E1
Chair castor suitability	EN425	yes, Typ W
Dimensional stability	EN434	≤ 0,1%
Thermal transmittance	EN12667	0,124 W/mK
Thermal resistance	EN12667	0,061 m <sup>2</sup> K/W

Suitable for hot water underfloor heating in accordance with standard specifications.

Suitable for professional floating installation.

Please follow our installation instructions for installation.

Status: December 2021; subject to change

